robot g coupe





RESTAURANTS - INSTITUTIONS - PASTRY CHEFS - DELICATESSENS - CATERERS



🜔 R 8 - R 10 - R 15 - R 20

ERGONOMIC

• See-through lid to monitor processing from start to finish.

Dishwasher-safe.

- Possibility of adding liquid or solid ingredients while Blixer is running.
- Central bowl locking system for **easy assembly.**
- Quick and easy lid attachment and removal.

COMFORT

- New bowl handle design for an even better grip.
- Handle at the back of the machine easier to move machine around.
- Lid fitted with a seal so that it is totally leakproof.

PERFORMANCE

- Stainless-steel, bowl-base blade assembly featuring new blade profile exclusive to Robot-Coupe, for homogeneous mixing and optimum cutting quality.
- Tall bowl shaft for processing liquid ingredients.

POWER

• Extremely powerful **induction motor** designed to withstand intensive use, thus ensuring a high level of reliability and a longer lifespan.

Supplied with:



Smooth-edged blade assembly.

HYGIENE

- All the parts can easily be removed, making the machine simpler to clean.
- Flat, easy-clean motor base.

robot @ coupe

R15

robot ** coupe

6

Optional extra:



nilable as an optional extra for **kneadi**

Coarse-serrated blades available as an optional extra for kneading and grinding Sine corrected blades available as an optional extra for sheaping

Fine-serrated blades available as an optional extra for chopping parsley.





Table-Top Cutter Mixers Vertical Cutter Mixers



The Products Plus:

Performance:

- The pulse control keeps you in command and allows you to maintain the precision cut that you require.
- A patented blade assembly, an exclusive Robot-Coupe feature, gives perfect results for small or large quantities

Fast:

- Less than 2 minutes are needed to make a bowl of mayonnaise, a steak tartare, a carrot puree or a fruit compote.
- Its fast processing speed gives free rein to Chefs.

Reliables:

- Industrial induction motor for heavy duty to guarantee longer life machine and reliability.
- From their simple and robust technical conception, the cutters have been built to exacting hygiene and safety standards.
- Parts in contact with food are easy to remove and to clean.









ROBOT-COUPE offers the most complete range of cutters with capacities ranging from 2.9 litre to 60 litre.





MINI BOWL

Stainless-steel bowl with 3.5-litre capacity for the R 8 and 4-litre capacity for the R 10 / R 15 (an exclusive patented ROBOT-COUPE feature) can be used to prepare sauces in no time, and chopped condiments and carry out all types of last minute preparations.





VACUUM

Machine pre-equipped to take vacuum "sous-vide" kit, simply attach the vacuum kit R-VAC[®], patented by Robot Coupe, to the lid and connect to a vacuum pump.

This vacuum kit, R-VAC[®], allows liquids to be added while processing. Vacuum processing allows you to obtain better results by giving :

- longer shelf life
- retention of flavors
- fresh presentation and all naturally without additives.

R-MIX FUNCTION

- For mixing delicate ingredients together without chopping them up.
- Take advantage of the R-Mix function, with its reverse-rotation, 60-500 rpm variable speed system, to mix wafer-thin slices of meat, incorporate whole crayfish tails in your terrines, dot your brioche cakes with raisins, fold in diced or cubed vegetables, etc.









We have cutters to meet your every need

How many covers do you serve per day ?			50 to 250	50 to 300	
What maximum bowl load per batch do you require ?	Up to 4.5 kg	Up to 6 kg	Up to 9 kg	Up to 12 kg	
Coarse mincing	3.0 kg	4.0 kg	6.0 kg	8.0 kg	
Emulsion	4.5 kg		9.0 kg	12.0 kg	
Kneading	ng 4.0 kg		7.0 kg	10.0 kg	
Grinding	nding 2.0 kg		5.0 kg	6.0 kg	



R 8 - R 8 V.V.

R 20 - R 20 V.V.

	Electrical data					Weight (kg)	
CE Mark	Speed (rpm)	Power (Watts)	Intensity (Amp.)	Voltage* (Amp)	Stainless-steel bowl capacity (litre)	net	gross
R 8	1 500 and 3 000	2 200	5,5	400 V/50 Hz / 3	8	40	52
R 8 V.V.	300 to 3 500	2 200	21	200-240 V/50-60 Hz / 1	8	40	52
R 10	1 500 and 3 000	2 600	6	400 V/50 Hz / 3	11.5	45	57
R 10 V.V.	300 to 3 500	2 600	21	200-240 V/50-60 Hz / 1	11.5	45	57
R 15	1 500 and 3 000	3 000	6,5	400 V/50 Hz / 3	15	49	62
R 15 V.V.	300 to 3 500	3 000	21,7	200-240 V/50-60 Hz / 3	15	49	62
R 20	1 500 and 3 000	4 400	10,1	400 V/50 Hz / 3	20	75	88
R 20 V.V.	300 to 3 500	4 400	24,8	200-240 V/50-60 Hz / 3	20	75	88

*Other voltages available.

	Dimensions (in mm)							
	Α	В	С	D	E	F	G	Н
R 8 - R 8 V.V.	585	445	255	300	315	525	545	645
R 10 - R 10 V.V.	660	520	280	300	345	600	560	720
R 15 - R 15 V.V.	680	540	300	340	370	620	615	740
R 20 - R 20 V.V.	760	620	315	340	380	700	630	820



robot Ø coupe°

HEAD OFFICE, FRENCH, EXPORT AND MARKETING DEPARTMENT: Tel.: + 33 1 43 98 88 33 - Fax: + 33 1 43 74 36 26 email: international@robot-coupe.com

Robot Coupe Australia: Tel.: (02) 9478 0300 - Fax: (02) 9460 7972 New Zealand: Tel.: 0800 716161 - Fax: 0800 716162 email: orders@robotcoupe.com.au

Robot Coupe U.K. LTD: Tel.: 020 8232 1800 - Fax: 020 8568 4966 2, Fleming Way, Isleworth, Middlesex TW7 6EU email: sales@robotcoupe.co.uk

Robot Coupe U.S.A.: Tel.: 1-800-824-1646 - Fax: 601-898-9134

email: info@robotcoupeusa.com - website: www.robotcoupeusa.com www.robot-coupe.com

DISTRIBUTOR

STANDARDS:

Machines in compliance with :

- The following European directives and related national legislation: 2006/42/CE, 2014/35/UE, 2014/30/UE, 2011/65/ UE, 2012/19/UE, CE N° 1935/2004, UE N° 10/2011.
- The following European harmonized standards and standards setting out health and safety rules: EN ISO 12100:2010, EN 60204-1:2006, EN 60529: IP 55, IP 34, EN 1678, EN 12852.

DEEE

488 - 07/2018 - Anglais

: 451

Réf.